



## PATENT ABSTRACTS OF JAPAN

(11) Publication number: 07138584 A (43) Date of publication of application: 30.05.1995

(51) Int. CI C10L 3/05 B01D 53/14

(21) Application number: 05288476 (22) Date of filing: 17.11.1993

(54) METHOD AND APPARATUS FOR TREATING BOG VAPORIZED IN LNG STORAGE EQUIPMENT

(57) Abstract.

PURPOSE. To reduce the equipment cost and operating cost by dispensing with the use of a compressor which is expensive and consumes much electric power.

CONSTITUTION: The poperatus consists of an absorption tower 2 in which BOG 61 field strough a Sosorption tower 2 in which BOG 61 field strough a Sodischarge line L2 is absorbed by an absorbem 9 to form a BOG sharobert solution 91, a stripping via 3 in which the BOG dissorbem solution 91 led through sharobert solution discharge line L2 is exercise line L3 in which the heated to strip the BOG of form a stripped BOG 81a, an absorbem technick line L3 for through which the (71) Applicant: KOBE STEEL LTD (72) Inventor. TORI TAMOTSU

softem 9 regenerated by stripping BOG 81 in the tower 3 is fed back to the absoration tower 2, and a heat exchange 12 in which heat exchange between LNG 8 lade through an LNG discharge line L1 from an LNG tank 1 and the absorbent 9 flowing through the absorbent feedback line L5 is effected and which is installed in the absorbent reduces kine L5.

COPYRIGHT: (C)1995, JPO

